

Model		LBx24-2043-xxx	LBx42-2043-xxx
Print	Technology (x)	D - Direct Thermal T - Thermal Transfer	D - Direct Thermal T - Thermal Transfer
	Width (max)	2.2" / 56mm	4.1" / 104mm
	Length (max)	40", 1016mm at 203 dpi 160", 4,064mm at 101 dpi	20" 513mm at 203 dpi (300 dpi optional) 80" 2,032mm at 101 dpi
	Speed (max)	3 ips 76mm/sec	3 ips 76mm/sec
	Resolution	Selectable 101 or 203 dpi	Selectable 101 or 203 dpi (300 dpi optional)
Media	Width	1" - 2.4" / 25 - 61mm	2" - 4.3" / 50 - 109mm
	Roll Diameter	4.7" / 119mm	4.7" / 119mm
	Ribbon Length	3150" / 80m (BT models only)	3150" / 80m (BT models only)
	Indexing	Black bar, notch, and gap	Black bar, notch, and gap
Bar Codes	Types Supported	21 standard bar codes, including: Add2, Add5, Codabar, Code39, Code93, Code128A/B/C, D2of5, I2of5, S2of5, EAN8/8+, EAN13/13+, EAN128, Maxicode, MSI/I1, PDF417, Plessey, Postnet, UPCA/A+/E/E1	
Fonts	Bitmapped	7 styles with up to 10 x 10 magnification, variable boldness and spacing	
	International AGFA Fonts	Sans-serif font in 7 pt. sizes, up to 4 x 4 magnification, variable boldness and spacing	
	Scalable Smooth Fonts	3 Ultra Font styles for smooth characters in any size and boldness	
	Rotations	0, 90, 180, 270 degrees	0, 90, 180, 270 degrees
Graphics	Features	Foreground and background logos and graphics	
	Formats	PCX, BMP	PCX, BMP
Memory	RAM	2 MB	2 MB
	Flash	4MB	4MB
Communications	Standard	Serial or parallel	Serial and parallel
	Ethernet	Internal option	Internal option
Electrical		100, 120, or 230 VAC, 50/60Hz	100, 120, or 230 VAC, 50/60Hz
Environmental	Operating	41°F to 104°F 5°C to 40°C	41°F to 104°F 5°C to 40°C
	Storage	-4°F to 122°F (-20°C to 50°C), 25-85% non-condensing RH	
Dimensions	Width BT	5.0" 127mm	6.8" 173mm
	Width BD	4.7" 119mm	6.8" 173mm
	Height	6.1" 155mm	6.1" 155mm
	Depth	9.4" 238mm	9.4" 238mm
Weight	BT	3.9 lbs 1.77kg	4.4 lbs 2.0kg
	BD	3.1 lbs 1.41kg	3.9 lbs 1.77kg
Accessories	Supplied	Quick Start Guide, power supply, CD including: Windows drivers, programmer's guide, Nicelabel label design software, inControl software	
	Options	Communications cables, annual service contracts, label dispenser, label cutter, Ethernet connectivity, real-time clock.	
Typical Printhead Life		2,000,000" 50km	2,000,000" 50km

Cognitive SOLUTIONS INC.

For additional information about Cognitive products, contact our offices or visit our website at www.cognitive.com

USA

Cognitive Solutions Inc.
4403 Table Mountain Dr Suite A
Golden, CO 80403
Tel: +1 303 273 1400
Toll free: +1 800 525 2785
Fax: +1 303 273 1414
sales@cognitive.com

South America

Selis S.A.*
Av. de Mayo 963 1º piso
Buenos Aires C1084AAE
Argentina
Tel: +54 11 4345 1443
FAX: +54 11 4343 7519
sasales@cognitive.com

Europe

Maxatec*
Atlantic Street
Altrincham, Cheshire
WA14 5QJ UK
Tel: +44 161 942 7850
Fax: +44 161 927 7664
europesales@cognitive.com

Asia-Pacific

DH Technology*
PO Box 726
Level 3, 39 Leighton Place
Hornsby NSW 2077 Australia
Tel: +61 2 9477 1999
Fax: +61 2 9477 1453
asiastales@cognitive.com

Vantex Technology*
635 Great South Road
Penrose Auckland
New Zealand
Tel: +64 9 571 0775
Fax: +64 9 571 0776
www.vantex.co.nz

Japan

CJP*
2-23-2 Higashi-Ikebukuro
Toshima-KU
Tokyo 170 Japan
Tel: +81 35 391 7689
Fax: +81 35 391 7692
japansales@cognitive.com

Copyright© 2006, Cognitive.
All rights reserved. Specifications, dimensions, and diagrams are subject to change without notification. Windows® is a registered trademark of Microsoft Corporation. AGFA® is a registered trademark of Miles, Inc.

